

# TECHNICAL INFORMATION 2022



	CU 15	CU 60	CU 150	CU 500
<b>External dimensions (in mm)</b>				
Length	415	700	860	1200
Width	335	500	625	800
Height	385	485	800	940
<b>Internal dimensions (in mm)</b>				
Length	335	510	640	990
Width	275	415	410	590
Height	325	325	620	760
<b>Payload capacity (in liters)</b>	17	67	160	443
<b>Tare weight (kg)</b>	2	7,8	21	41
<b>*Total weight for Model F</b>	8,8	21,9	39,8	97
<b>*Total weight for Model C</b>	4,5	14,8	35	78

(\*Including PCM-elements)

# USAGE INFORMATION 2022



## CU 15

	PCM AMOUNT	INTERNAL TEMPERATURE	PCM PLACEMENT	APPROX. UPTIME
CU 15 C	2	+2°C .. +8°C	IN THE LID	25H
CU 15 F	5	< -18°C	SIDE POCKETS AND LID	15H

## CU 150

	PCM AMOUNT	INTERNAL TEMPERATURE	PCM PLACEMENT	APPROX. UPTIME
CU 150 C	2	+2°C .. +8°C	SIDE POCKETS AND OPPOSITE CORNERS	24H
CU 150 F	4	< -18°C	SIDE POCKETS AND LID	15H

## CU 60

	PCM AMOUNT	INTERNAL TEMPERATURE	PCM PLACEMENT	APPROX. UPTIME
CU 60 C	1	+2°C .. +8°C	IN THE LID	20H
CU 60 F	3	< -18°C	SIDE POCKETS AND LID	14H

## CU 500

	PCM AMOUNT	INTERNAL TEMPERATURE	PCM PLACEMENT	APPROX. UPTIME
CU 500 C	8	+2°C .. +8°C	SIDE POCKETS	60H
CU 500 F	12	< -18°C	SIDE POCKETS	24H